

Control Stations

Operating Heads for Control Stations

Metal Operating Heads for use with RC•P & RC•M enclosures - IP65



Description	Knob Size	Colour	
Flush Push Button Spring Return		○ White	RM2-BA1
		● Black	RM2-BA2
		● Green	RM2-BA3
		● Red	RM2-BA4
		● Yellow	RM2-BA5
		● Blue	RM2-BA6
		⬇ Black Arrow on White base	RM2-BA334
		⬆ White Arrow on Black base	RM2-BA335
Recess (Guarded) Push Button		○ White	RM2-BA16
		● Black	RM2-BA26
		● Green	RM2-BA36
		● Red	RM2-BA46
		● Yellow	RM2-BA56
		● Blue	RM2-BA66
		Projecting Push Button Spring Return	
● Black	RM2-BL2		
● Green	RM2-BL3		
● Red	RM2-BL4		
● Yellow	RM2-BL5		
● Blue	RM2-BL6		
Booted Push Button Spring Return IP66			
		● Black	RM2-BP2
		● Green	RM2-BP3
		● Red	RM2-BP4
		● Yellow	RM2-BP5
		● Blue	RM2-BP6
		Flush Push Button Spring Return with Transparent Boot IP66	
● Black	RM2-BA28		
● Green	RM2-BA38		
● Red	RM2-BA48		
● Yellow	RM2-BA58		
● Blue	RM2-BA68		
Mushroom Head Push Button Spring Return	φ 40mm φ 60mm		
		● Green	RM2-BC3
		● Red	RM2-BC4
		● Yellow	RM2-BC5
		● Blue	RM2-BC6
		● Red	RM2-BR4
		Mushroom Head Push Button Turn to Release	φ 30mm φ 40mm φ 60mm
● Red	RM2-BS54		
● Red	RM2-BS64		
Mushroom Head Push Button Key Release - Key No. 455	φ 40mm	● Red	RM2-BS14
Mushroom Head Push Button	φ 40mm	● Red (Pre Marked)	RM2-BT4
Push to Stay and Pull to Release		● Red	RM2-BT43

Operating Heads with Black metal bezel

TO Order add Suffix '7' to above e.g. RM2-BA1 Becomes RM2-BA17

Control Stations

Characteristics

General Characteristics	
Products	Control Stations
Reference Standard	IEC 60947-5-1, EN 60947-5-1, IEC 337-1, UL 508, CSA C-22-2 n° 14
Approval	UL, cUL, CSA, CE
Protection Degree	IP 65 / IP 66 (as per IEC), NEMA 4 / 4X (special version)
Ambient Temperature	-40°C ~ + 70°C (Storage) -25°C ~ + 70°C (Operation)
Vibration Resistance	15g (40 Hz < frequency < 500 Hz) conforming to IEC 68-2-6
Shock Resistance	Push Buttons : 70g, Mushroom Head Push Buttons : 15g, Selector Switches : 200g conforming to IEC 68-2-27
Material and Colour	Thermoplastic - grey lid and black base for 1,2,3,4 way, yellow lid & black base for one way Aluminium Die Cast - grey lid and dark grey base
Cable Entry	Knock-outs provided