



# robusta (9A ~ 95A)

## 3 & 4 Pole Contactors with DC operating coil Characteristics

### General Characteristics

Type		Unit	TP1-D09 ~ TP1-D80	
Rated insulation voltage (Ui)	IEC 60947-4-1	V	1000	
Conforming to standards			NFC EN 60947, VDE0660, BSEN60947, IEC 60947 & IS 13947	
Approvals			UL, CSA	
Degree of Protection	Conforming to VDE 0106		Protection against direct finger contacts	
Protective treatment	Standard version		“TH”	
Ambient air temperature (around the device)	Storage	°C	-60 to +80	
	Operation	°C	-5 to +55 (0.8 to 1.1Uc)	
	Permissible	°C	-40 to +70, for operation at Uc	
Maximum operating altitude	Without derating	Mtr.	3000	
Operating Position	Without derating		+30° possible, in relation to normal vertical mounting plane	

### Pole Characteristics

Type	TP1-	Unit	D09	D12	D18	D22	D25	D32	D38	D40	D50	D65	D80
Number of poles (Power)			3 or 4	3 or 4	3	3	3 or 4	3	3	3 or 4	3 or 4	3 or 4	3 or 4
Power + Auxiliary			3+1	3+1	3+1	3+1	3+1	3+1	3+1	3+2	3+2	3+2	3+2
Rated current (Ie)	AC3 up to 440V @ 55°C	A	9	12	18	22	25	32	38	40	50	65	80
Rated operating Voltage (Ue)	Up to	V	690	690	690	690	690	690	690	690	690	690	690
Frequency limits	Of the operational current	Hz							25-400				
Rated thermal current (Ith)	θ < 40°C	A	25	25	32	32	45	50	50	60	80	80	125
Rated making capacity	Irms conforming to IEC-60947-4	A	250	250	300	300	450	550	550	800	900	1000	1100
Rated breaking capacity	Irms conforming to IEC-60947-4	A	250	250	300	300	450	550	550	800	900	1000	1100
	500V	A	175	175	250	250	400	450	450	800	900	1000	1000
	660-690V	A	85	85	120	120	180	180	180	400	500	630	640
Average impedance per pole	At Ith and 50Hz Milli Ω	Max.	2.5	2.5	2.5	2.5	2	2	2	1.5	1.5	1	0.8
Power dissipation per pole for AC-3		W	0.2	0.36	0.8	0.8	1.25	2	2	2.4	3.7	4.2	5.1
the above operational currents													

### Control Circuit Characteristics

Type		Unit	TP1-D09~D22	TP1-D25~D38	TP1-D4011~D65	TP1-D80
Rated control circuit voltage (Uc)	DC	V	12 to 660		12 to 660	
Control voltage limits ( $\theta < 55^\circ\text{C}$ )	Operational	Standard Coil	0.8 - 1.1 Uc		0.85 - 1.1 Uc	
		Wide Range Coil	0.7 - 1.25 Uc		0.75 - 1.25 Uc	
Average consumption DC at 20°C and at Uc	Drop out		0.1 - 0.25 Uc		0.1 - 0.3 Uc	
	DC	Inrush	W	9	11	22
		Sealed	W	9	11	22
Average operating time at Uc	Closing time "C"	msec	40-48	52-64	85-110	95-130
	Opening time "O"	msec	6-14	8-14	20-35	20-35
Mechanical life Uc (mechanical durability)	In millions of operating cycles		30	25	20	20
Maximum operating rate (at ambient temp. of $\theta < 55^\circ\text{C}$ )	In operating cycle/hour		3600	3600	3600	3600

### Integral Auxiliary Contact Characteristics

Type		Unit	TP1- D09 ~ TP1- D80
Rated thermal current (Ith)	θ < 40°C	A	10
Rated operational voltage (Ue)	Up to	V	660

B